INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 49, 1976

AUTHOR INDEX

ABE, M., see KURATA, M., (5) 1276, 1290
ADAMS, H. E., see ANDERSON, J. N., (5) 1238
——, see BACZEK, S. K., (5) 1250
AGEE, R. D., J. L. BROWNLEE, E. SCHARY, AND T. L. TOLBERT, Response of radial passenger tire treadwear to reinforcing cord modulus (Abstract), (2) 400
ALLEN, G., P. L. EGERTON, AND D. J. WALSH, Model polyurethane networks, (5) 1206
ALSYS, C. M., Injection molding of TP elastomers at Fisher Body Syracuse (Abstract), (5) 1355
ANDERSON, J. N., The distribution of olefinic linkages in elastomers, (4) 992
——, see BACZEK, S. K., (5) 1250
——, S. K. BACZEK, H. E. ADAMS, AND L. E. VESCELIUS, Functionality distribution of hydroxyl-terminated polybutadienes by gel permeation chromatography. I. Method and calibration procedure, (5) 1238
ARCONTI, R. J., see PIERSON, R. M., (5) 1363
ATHEY, R. J., see VAN GULICK, N. M., (2) 320
AVGEROPOULOS, G. N., F. C. WEISSERT, G. G. A. BÖHM, AND P. H. BIDDISON, Heterogeneous polymer blends. I. Rheology and morphology, (1) 93
——, see WEISSERT, F. C., (2) 392

BACZEK, S. K., see ANDERSON, J. N., (5) 1238
——, J. N. ANDERSON, AND E. H. ADAMS, Functionality distribution of hydroxyl-terminated polybutadienes by gel permeation chromatography. II. Measurements for commercial polymers, (5) 1250
BALDWIN, F. P., see GARDNER, I. J., (2) 391
——, I. J. GARDNER, J. A. RAE, AND A. MALATESTA, Polyisobutylene-based elastomers containing conjugated diene functionality (Abstract), (2) 390
BANKS, S. A., J. D. BRILLINGER, C. A. COFFEY, R. C. Puydak, AND G. N. SCHMIT, Environmental qualities of thermoplastic elastomers (Abstract), (5) 1355
BARON, O., D. BRICHZIN, AND E. BÖTTCHER, Contribution for better uniformity of elastomer blend compounds (Abstract), (2) 399
BEATTY, J. R., AND V. L. FOLT, Physical properties and service performance of oil-extended natural rubber in heavy-duty tire treads (Abstract), (5) 1362
BERET, S., AND J. M. PRAUSNITZ, Pressure–volume–temperature measurements for polyethylene, polyisobutylene, poly(vinyl acetate), and poly(dimethylsiloxane) to 1 kilobar, (2) 200
—— AND ——, Densities of amorphous polymers at high pressures, (2) 207
BIDDISON, P. H., see AVGEROPOULOS, G. N., (1) 93
BISIO, A. L., AND J. V. FUSCO, Marketing new products today (Abstract), (5) 1356.
BÖHM, G. G. A., see AVGEROPOULOS, G. N., (1) 93
——, see WEISSERT, F. C., (2) 392
BOOZER, C. E., F. R. ELKINS, AND H. J. GROS, Processing characteristics of new particulate polymers (Abstract), (5) 1350
BORZENSKI, F. J., A comparative study of performance of batch and continuous mixers (Abstract), (2) 403
BÖTTCHER, E., see BARON, O., (2) 399
BOYER, A. H., see MERCER, H. N., (4) 1068
BRAME, E. G., JR., see KHAN, A. A., (2) 394
BRICHZIN, D., see BARON, O., (2) 399
BRILLINGER, J. H., see BANKS, S. A., (5) 1355

Brizzolara, D. F., W. Honsberg, and R. W. Keown, Polychloroprene carboxylated latex (Abstract), (2) 412
Brown, R. J., see Parks, C. R., (2) 233
Brownlee, J. L., see Agee, R. D., (2) 400
Brusky, P. L., see Mercer, H. N., (4) 1068
Bruzzone, M., see Cesca, S., (4) 937
Buckley, D. J. Sr., see Cohen, H., (4) 967
——, see Thaler, W. A., (4) 960
Bull, A. L., and G. Holden, Use of thermoplastic rubbers in blends with other plastics (Abstract), (5) 1351
Burg, G. R., D. S. Winkler, and H. L. Stephens, Silane modification of nonblack fillers in elastomers (Abstract), (2) 397
Burgoyne, M. D., G. R. Leaker, and Z. Krekic, The effect of reusing ground flash and scrap rubber in parent compound, (2) 375
Burroughs, A. E., see Pelosi, L. F., (2) 367
Burton, G. W., and C. P. O'Farrell, Preparation of artificial latexes (Abstract), (2) 394

Calihan, L. E., see Schulz, D. N., (1) 126
Capizzi, A., see Gianotti, G., (1) 170
Carlson, D. W., see Rogers, J. W., (5) 1364
Caruso, P. P., see van Gulick, N. M., (2) 320
Caruthers, J. M., R. E. Cohen, and A. I. Medalia, Effect of carbon black on hysteresis of rubber vulcanizates: equivalence of surface area and loading, (4) 1076
Causa, A. G., see Vorachek, J. J., (2) 414
Cesca, S., M. Bruzzone, A. Priola, G. Ferraris, and P. Giusti, Copolymerization of isobutene and isoprene at "high" temperature with syncatalyst systems based on aluminum organic compounds, (4) 937
Chang, B., see Larsen, J. W., (4) 1120
Chen, I. J., see Reber, D., (1) 28
Coffey, C. A., see Banks, S. A., (5) 1355
Cohen, R. E., see Caruthers, J. M., (4) 1076
Cohen, H., J. A. Rae, and D. J. Buckley, Sr., High-molecular-weight, high-unsaturation copolymers of isobutylene and conjugated dienes. II. Properties and performance, (4) 967
Collins, E. A., see Nakajima, N., (1) 52
——, C. A. Daniels, and J. A. Davidson, Factors affecting the properties and rheological behavior of latex (Abstract), (2) 411
Cooper, S. L., see Lilaonitkul, A., (5) 1357
Coran, A. Y., P. Hamed, and L. A. Goettler, The mechanical behavior of short-fiber–elastomer composites, (5) 1167
Cornell, W. H., L. B. Kliever, and D. D. Dearmont, Mixing of thermoplastic sytrene–butadiene elastomers (Abstract), (2) 399
Coulthard, D. C., and W. D. Gunter, New compounding approaches to heat-resistant NBR (Abstract), (2) 407
Cox, W. J., Environmental and OSHA considerations (Abstract), (2) 413

Daniels, C. A., see Collins, E. A., (2) 411
Davidson, J. A., see Collins, E. A., (2) 411
——, see Woods, M. E. (1) 112
Dearmont, D. D., see Cornell, W. H., (2) 399
Del Giudice, L., see Gianotti, G., (1) 170
Devine, M. L., see Mercer, H. N., (4) 1068
Dietrick, M. I., D. E. Emmert, and D. A. Lederer, Optimization of wire adhesion by varying concentration of bonding agents and cure rate (Abstract), (2) 409
Dizon, E. S., Processing in an internal mixer as affected by carbon black properties, (1) 12
Djiauw, L. K., and D. G. Fesko, Elongation of painted high-modulus elastomers at low temperatures, (4) 1111
Ducháček, V., Effect of temperature on the course of thiuram-accelerated sulfur vulcanization, (5) 1193
Dunn, J. R., Blends of elastomers and thermoplastics—A review, (4) 978
——, and H. A. Pfisterer, Using simulated end-use conditions in assessing the high-temperature performance of oil-resistant vulcanizates (Abstract), (5) 1348

Ecker, H., see Kainradl, P., (2) 258
Elkins, F. R., see Boozer, C. E., (5) 1350

EGERTON, P. L., see ALLEN G., (5) 1206
EMMERT, D. E., see DIETRICK, M. I., (2) 409

FATH, M. A., Effect of EPDM matrix properties on resultant cellulose EPDM composite properties (Abstract), (5) 1363
FERRARIS, G., see CESCA, S., (4) 937
FESKO, D. G., see DJIAUW, L. K., (4) 1111
FETTERMAN, M. Q., Application of rubber compounding technology to thermoplastic forms of ethylene–vinyl acetate copolymers (Abstract), (5) 1359
FETTERS, L. J., Block and graft copolymers from olefinic monomers (Abstract), (5) 1351
——, see MORTON, M., (2) 303
FLEMING, R. A., see VORACHEK, J. J., (2) 414
FOGIEL, A. W., see MACLACHLAN, J. D., (1) 43
——, H. K. FRENSDORFF, AND J. D. MACLACHLAN, Shrinkage of cured fluoroelastomers. I. Basic parameters, (1) 34
FOLDI, A. P., Reinforcement of rubber through short individual filaments, (2) 379
FOLT, V. L., The preparation of tire treads in the factory: A rheological study (Abstract), (5) 1361
——, see BEATTY, J. R., (5) 1362
FRENSDORFF, H. K., see FOGIEL, A. W., (1) 34
FULLER, R. E., see HAGMAN, J. F., (2) 395
FUSCO, J. F., see BISIO, A. L., (5) 1356

GARDNER, I. J., see BALDWIN, F. P., (2) 390
—— AND F. P. BALDWIN, Interpenetrating networks from isobutylene copolymers containing conjugated diene functionality (Abstract), (2) 391
GATZA, P. E., see TOUCHET, P., (2) 396
GETSON, J. C., AND R. N. LEWIS, A silicone rubber composite reinforced by *in-situ* generated short fibers (Abstract), (2) 402
——, AND R. N. LEWIS, A silicone rubber composite reinforced by crosslinked in situ generated short fibers (Abstract), (5) 1364
GIANOTTI, G., A. CAPIZZI, AND L. DEL GIUDICE, *Cis*-polyoctenamer: Thermodynamic parameters of fusion and crystallization kinetics, (1) 170
GIURCO, F., see MILLS, W., (2) 291
GIUSTI, P., see CESCA, S., (4) 937
GLYMPH, E. M., Production and properties of low-ammonia centrifuged natural rubber latexes (Abstract), (2) 410
GOETTLER, L. A., see CORAN, A. Y., (5) 1167
GOODMAN, A. L., C. K. SHIH, A. C. L. SU, AND G. L. ZAISER, Blow-moldable copolyester elastomer (Abstract), (5) 1359
GÖRITZ, D., AND F. H. MÜLLER, Changes of state in polymeric networks during orientation. II. Analysis of elongation-induced crystallization by calorimetry, (2) 210
GOSWAMI, B. C., see LAMB, G. E. R., (5) 1145
GREENE, R. N., see HAGMAN, J. F., (2) 395
GROS, H. J., see BOOZER, C. E., (5) 1350
GROSCH, K. A., AND A. SCHALLAMACH, Tire friction on wet roads, (3) 862
GROVER, H. N., see SOMMER, J. G., (5) 1129
GUILLAUMOND, F.-X., The influence of the solubility of accelerators on the vulcanization of elastomer blends, (1) 105
GUNBERG, P. F., see TURETZKY, S. B., (1) 1
GUNTER, W. D., see COULTHARD, D. C., (2) 407
GURLEY, T. G., see PIERSON, R. M., (5) 1363
GWIN, L. E., AND E. J. WEAVER, A new dimension in rubber compound tackifiers (Abstract), (5) 1365

HAGMAN, J. F., R. E. FULLER, W. K. WITSIEPE, R. N. GREENE, AND K. J. LEWIS, Ethylene–acrylic elastomer—A new class of heat- and oil-resistant rubber (Abstract), (2) 395
HALE, K. L., see MCCORMICK, C., (5) 1365
HAMED, P., see CORAN, A. Y., (5) 1167
HANSEN, F. K., see UGELSTAD, J., (3) 536
HARMS, E. G., Capability of pin-type cold-feed extruder in rubber processing (Abstract), (2) 403
HARRINGTON, E. R., see SHELTON, J. R., (1) 147
HELFAND, E., Block copolymers, polymer–polymer interfaces, and the theory of inhomogeneous polymers, (2) 237

Hertel, E. S., and E. A. Storch, Impact of air-pollution control regulations on the design and construction of an organic-chemical manufacturing facility—A case study in Connecticut (Abstract), (5) 1354
Hillegass, D. V., see Pierson, R. M., (5) 1363
Holden, G., see Bull, A. L., (5) 1351
Homma, T., see Kurata, M., (5) 1290
Honsberg, W., see Brizzolara, D. F., (2) 412
Hopper, R. J., Improved cocure of EPDM—polydiene blends by conversion of EPDM into macromolecular cure retarder, (2) 341
Hsieh, H. L., Synthesis of radial thermoplastic elastomer, (5) 1305
Hummel, K., see Wewerka, D., (5) 1142

Igarashi, T., Mechanics of peeling of rubbery materials. I. Peel strength and energy dissipation, (5) 1200
Inomata, J., see Morton, M., (2) 303
Inselsbacher, W., see Wewerka, D., (5) 1142
Iwama, M., see Kurata, M., (5) 1276, 1290

Johnson, J. B., see Normand, R. J., (2) 407
Johnson, P. R., A general correlation of the flammability of natural and synthetic polymers, (1) 158
——, Polychloroprene rubber, (3) 650

Kachur, V., and E. J. Weaver, Rubber-to-cord dynamic adhesion test: development, analysis, and applications (Abstract), (5) 1349
——, and G. Kaufmann, Heat generation in pneumatic tires, (3) 823
Kainradl, P., F. Wolf, and H. Ecker, Variations in testing procedures on the rotary flexometer, (2) 258
Kalfayan, S. H., R. H. Silver, and S. T. Liu, Accelerated heat-aging studies on fluororubber in various media, (4) 1001
Kato, M. and J. E. Mark, The effect of temperature on the stress/strain isotherms of polyisobutylene networks at high elongation, (1) 85
Kaufmann, G., see Kainradl, P., (3) 823
Kelly, R. L., Overview of the latex industry (Abstract), (2) 410
Kenney, V. R. and G. R. Wienkoop, Digital computer control of the rubber calendering process (Abstract), (2) 399
Keown, R. W., see Brizzolara, D. F., (2) 412
Khan, A. A. and E. G. Brame, Jr., Preparation and characterization of copolymers of chloroprene and methyl methacrylate (Abstract), (2) 394
Kliever, L. B., see Cornell, W. H., (2) 399
Koenig, J. L., see Pecsok, R. L., (2) 405; (4) 1010
Krekic, Z., see Burgoyne, M. D., (2) 375
Kurata, M., M. Abe, M. Iwama, and M. Matsushima, Randomly branched polymers. I. Hydrodynamic properties, (5) 1276
——, H. Okamoto, M. Iwama, M. Abe, and T. Homma, Randomly branched polymers. II. Computer analysis of gel-permeation chromatograms, (5) 1290

Lamb, G. E. R., see Weigmann, H. D., (4) 1040
——, H. D. Weigmann, and B. C. Goswami, Studies of heat generation in polyester cord tires, (5) 1145
Lambiotte, J. F., The economics of thermoplastic rubbers (Abstract), (5) 1356
Larsen, J. W. and B. Chang, Conversion of scrap tires by pyrolysis in molten salts, (4) 1120
Lawrence, J. P., *N*-(aminothio)imide cure modifiers, (2) 333
Leaker, G. R., see Burgoyne, M. D., (2) 375
Lederer, D. A., see Dietrick, M. I., (2) 409
Leonard, M. H., Feedstocks for the rubber industry (Abstract), (5) 1353
Lewis, K. J., see Hagman, J. F., (2) 395
Lewis, R. N., see Getson, J. C., (2) 402; (5) 1364
Lilaonitkul, A., J. C. West, and S. L. Cooper, Properties of poly(tetramethylene oxide)–poly(tetramethylene terephthalate) block polymers (Abstract), (5) 1357
Lindeman, C. M., Beater deposition with latex (Abstract), (2) 414
Lipatov, Y. S., The structure and relaxation of thin polymer layers on solid surfaces, (5) 1311
Liu, S. T., see Kalfayan, S. H., (4) 1001

LOBAN, R. D., see SMITH, G. G., (1) 140
LU, M. T., Evaluation of some uncertainties in a computerized curing control system for rubber industry (Abstract), (2) 406

MACOSKO, C. W., s[illegible] MILLER, D. R., (5) 1219
——, see VALLES, E. M., (5) 1232
——, AND STARITA, J. M., A viscoelastic tester for rubber (Abstract), (5) 1367
MACLACHLAN, J. D., see FOGIEL, A. W., (1) 34
—— AND A. W. FOGIEL, Shrinkage of cured fluoro-elastomers. II. Shrinkage control, (1) 43
MALATESTA, A., see BALDWIN, F. P., (2) 390
MANABE, K., see NAKASHIMA, K., (5) 1324
MANERI, R. R., Earl L. Warrick, Charles Goodyear Medalist—1976
MARK, J. E., see KATO, M., (1) 85
MARTEAU, J., see PAUTRAT, R., (4) 1060
MARTINO, L. D., Carpet backfinishing review (Abstract), (2) 414
MATSUSHIMA, M., see KURATA, M., (5) 1276
MAUSSER, R. F., Vulcanization considerations (Abstract), (2) 413
MCCORMICK, C., J. R. WEST, AND K. L. HALE, Carbon-black-filled SBR compounds that achieve maximum tread wear, maximum skid resistance, and minimum heat buildup at minimum cost (Abstract), (5) 1365
MEDALIA, A. I., see CARUTHERS, J. M., (4) 1076
MERCER, H. N., A. H. BOYER, P. L. BRUSKY, AND M. L. DEVINEY, The third dimension of carbon black structure, (4) 1068
METIVIER, B., see PAUTRAT, R., (4) 1060
MEYER, D. A., AND J. A. WELCH, Design and engineering with natural rubber (Abstract), (5) 1362)
MILLER, D. R., AND C. W. MACOSKO, A new derivation of post-gel properties of network polymers, (5) 1219
MILLS, W. AND F. GIURCO, Compound processability and molecular weight distribution of SBR, (2) 291
MOGHE, S. R., Dynamic stress relaxometer, a new processability instrument, (2) 247
——, Mechanical properties of short-fiber–elastomer composites (5) 1160
MONTE, S. J., see SUGERMAN, G., (5) 1350
—— and G. SUGERMAN, Current developments in filled polymer systems with titanate coupling agents (Abstract), (2) 398
——, ——, AND D. J. SEEMAN, Titanium coupling agent—Newest developments (Abstract) (5), 1351
MORA, A., see STEPHANOPOULOS, G., (5) (1368
MORAN, A. L., see PELOSI, L. F., (2) 367
MORI, K., see NAKAMURA, Y., (4) 1031
MORITA, E., The reaction of *N*,4-dinitroso-*N*-methylaniline and polymers, (4) 1019
MORRISSEY, R. T., Sulfur-cure-compatible blends of halogenated ethylene–propylene copolymers and diene rubbers, (2) 363
MORTON, M., L. J. FETTERS, J. INOMATA, D. C. RUBIO, AND R. N. YOUNG, The synthesis and properties of uniform polyisoprene networks. I. Synthesis and characterization of α,ω-dihydroxypolyisoprene, (2) 303
MÜLLER, F. H., see GÖRITZ, D., (2) 210
MURTLAND, W. O., Considerations in petrochemical plant site selection (Abstract), (5) 1352

NAKAJIMA, N. AND E. A. COLLINS, Rheological characteristics of gum elastomers, (1) 52
NAKAMURA, T., see NAKAMURA, Y., (4) 1031
NAKAMURA, Y., K. MORI, AND T. NAKAMURA, Evaluation of 2-R-4,6-dithiol-s-triazine for neoprene vulcanization, (4) 1031
NAKASHIMA, K., AND K. MANABE, Solvent crack growth in NBR rubber, (5) 1324
NICHOLS, M. J. AND R. F. OHM, Compounding for elastomer adhesion. Part I. An alternative for hexamethylenetetramine in the HRH adhesion system (Abstract), (2) 408
—— AND ——, Compounding for elastomer adhesion. Part II. An alternative for resorcinol in the HRH adhesion system (Abstract), (2) 409
NORMAND, R. J. AND J. B. JOHNSON, Heat resistance of CPE elastomers (Abstract), (2) 407

O'FARRELL, C. P., see BURTON, G. W., (2) 394
OHM, R. F., see NICHOLS, M. J., (2) 408, 409
OKAMOTO, H., see KURATA, M., (5) 1290

Painter, P. C., see Pecsok, R. L., (2) 405; (4) 1010
Parks, C. R., and R. J. Brown, Crosslink density of elastomers. A new gas-chromatographic method, (2) 233
Patel, H. P., J. L. Turner, and J. D. Walter, Radial tire cord-rubber composites, (4) 1095
Pautrat, R., B. Metivier, and J. Marteau, Contribution to the identification and quantitative determination of carbon black in vulcanizates by thermogravimetric analysis, (4) 1060
Pecsok, R. L., P. C. Painter, J. R. Shelton, and J. L. Koenig, Fourier-transform infrared studies of the mechanism of oxidation of *cis*-1, 4-polybutadiene, (Abstract) (2) 405; (4) 1010
Pelosi, L. F., A. L. Moran, A. E. Burroughs, and T. L. Pugh. The volatile products evolved from fluoroelastomer compounds during curing, (2) 367
Peterson, A. L., see Rogers, T. H., (5) 1360
Pfisterer, H. A., see Dunn, J. R., (5) 1348
Pierson, R. M., T. G. Gurley, D. V. Hillegass, and R. J. Arconti, Research on uses of rubber in the cardiovascular system (Abstract), (5) 1363
Prausnitz, J. M., see Beret, S., (2) 200, 207
Priola, A., see Cesca, S., (4) 937
Pugh, T. L., see Pelosi, L. F., (2) 367
Puydak, R. C., see Banks, S. A., (5) 1355

Rae, J. A., see Baldwin, F. P., (2) 390
——, see Cohen, H., (4) 967
Ratliff, O. D., Fiber-reinforced rubber for air cylinder packing cups (Abstract), (5) 1360
Reber, D., I. J. Chen, and K. J. Siwiecki, Relationship between operating variables and temperature of elastomer entering the mold on a coaxial screw/pot injection molding machine, (1) 28
Richardson, M. J., and N. G. Savill, Derivation of accurate glass transition temperatures by differential scanning calorimetry, (2) 224
Ritchie, K., and R. J. Weir, Heat resistance and dynamic characteristics of bromobutyl-modified elastomer blends (Abstract), (2) 408
Roddy, E. J., New applications and design concepts for thermoplastic copolyester elastomers (Abstract), (5) 1358
Rogers, J. W., and D. W. Carlson, Fiber-loaded V-belt compounds (Abstract), (5) 1364
Rogers, T. H., and A. L. Peterson, Control of South American leaf blight on a plantation scale (Abstract), (5) 1360
Rosenberg, W. S., A review of the national pollutant discharge elimination system for new and existing sources (Abstract), (5) 1356
Rubio, D. C., see Morton, M., (2) 303
Rusch, K. C., High-modulus elastomers for flexible exterior automotive body components (Abstract), (5) 1365

Sato, H., see Tanaka, Y., (5) 1259, 1269
Savill, N. G., see Richardson, M. J., (2) 224
Schallamach, A., see Grosch, K. A., (3) 862
Schary, E., see Agee, R. D., (2) 400
Schmit, G. N., see Banks, S. A., (5) 1355
Schulz, D. N., L. E. Calihan, and D. P. Tate, Solution-SBR powders, (1) 126
Schweller, H. E., Latex foam automotive body seals (Abstract), (2) 413
Seeman, D. J., see Monte, S. J., (5) 1351
——, see Sugerman, G., (5) 1350
Sheeler, J. W., Glass fibers as reinforcement for elastomeric compounds (Abstract), (5) 1360
Shelton, J. R., see Pecsok, R. L., (2) 405; (4) 1010
—— and E. R. Harrington, The role of certain organic sulfur compounds as preventive antioxidants. II. Activity as peroxide decomposers and effects of bases, (1) 147
Shih, C. K., see Goodman, A. L., (5) 1359
Silver, R. H., see Kalfayan, S. H., (4) 1001
Simpson, B. D., Adhesive applications of radial block copolymers (Abstract), (5) 1352
Siwiecki, K. J., see Reber, D., (1) 28
Smith, B. R., Measurement of molecular weight distribution of SBR and prediction of rubber processability, (2) 279
Smith, G. G., and R. D. Loban, Effects of molybdenum disulfide on elastomer flex life and other properties, (1) 140

SMITH, T. L., Tensile strength of polyurethane and other elastomeric block copolymers, (1) 64
SOMMER, J. G., H. N. GROVER, AND P. T. SUMAN, In-place cleaning of rubber curing molds, (5) 1129
SON, P. N., The chemistry of phthalic anhydride in cure retardation of rubbers, (1) 118
SPOO, B. H., Injection molding of high-performance fluoroelastomers (Abstract), (5) 1350
STACHOWIAK, R. W., Consideration, design, and operation of a verastile stereopolymer semiworks facility (Abstract), (5) 1353
STARITA, J. M., see MACOSKO, C. W., (5) 1367
STEIN, R. S., Rheo-optical studies of rubbers, (3) 458
STEPHANOPOULOS, G., AND A. MORA, Mathematical modeling of the rubber industry (Abstract), (5) 1368
STEPHENS, H. L., see BURG, G. R., (2) 397
STORCH, E. A., see HERTEL, E. S., (5) 1354
SU, A. C. L., see GOODMAN, A. L., (5) 1359
SUGERMAN, G., see Monte, S. J., (2), 398; (5) 1351
——, S. J. MONTE, AND D. J. SEEMAN, Cumylphenol derivatives (Abstract), (5) 1350
SUMAN, P. T., see SOMMER, J. G., (5) 1129
SUTTON, N. E., AND JAMES Q. WOOD, Design and operating considerations for overseas synthetic rubber plants (Abstract), (5) 1353
SVANSON, S. E., see SVENSSON, L. G., (5) 1182
SVENSSON, L. G., AND S. E. SVANSON, A broad-line NMR investigation of isoprene rubber filled with carbon black, (5) 1182

TANAKA, Y., AND H. SATO, Sequence distribution of polyisoprenes, (5) 1259
—— AND ——, Sequence distribution of *cis*-1,4- and *trans*-1,4-units in polyisoprenes, (5) 1269
TATE, D. P., see SCHULZ, D. N., (1) 126
THALER, W. A., AND D. J. BUCKLEY, SR., High-molecular-weight, high-unsaturation copolymers of isobutylene and conjugated dienes. I. Synthesis, (4) 960
TIELKING, J. T., General deformations of membrane structures (Abstract), (2) 400
TOLBERT, T. L., see AGEE, R. D., (2) 400
TOUCHET, P., AND P. E. GATZA, Phosphazene elastomers for fuel service under arctic conditions (Abstract), (2) 396
TREXLER, H. E., Elastomer blends—Dependence of properties on the nature of the polymers and the cure systems (Abstract), (2) 392
TURETZKY, S. B., P. R. VAN BUSKIRK, AND P. F. GUNBERG, Quantitative evaluation of emulsion styrene–butadiene rubbers and compounding variables by controlled mixing, (1) 1
TURNER, J. L., see PATEL, H. P., (4) 1095

UGELSTAD, J., AND F. K. HANSEN, Kinetics and mechanism of emulsion polymerization, (3) 536
URANECK, C. A., Molecular weight control of elastomers prepared by emulsion polymerization, (3) 610

VALLES, E. M., AND C. W. MACOSKO, The effect of network structure in the equation of rubber elasticity, (5) 1232
VAN BUSKIRK, P. R., see TURETZKY, S. B., (1) 1
VAN GULICK, N. M., J. J. VERBANC, P. P. CARUSO, AND R. J. ATHEY, Coordination complexes of 4,4′-diaminodiphenylmethane—Chemistry and applications, (2) 320
VERBANC, J. J., see VAN GULICK, N. M., (2) 320
VESCELIUS, L. E., see ANDERSON, J. N., (5) 1238
VICKEY, G. C., Mixing preparticulated rubbers and predispersed pigments for improved uniformity (Abstract), (2) 404
VLASAK, R. L., AND H. A. VOGEL, Production of high-performance fluorelastomers (Abstract), (5) 1357
VOGEL, H. A., see VLASAK, R. L., (5) 1357
VORACHEK, J. J., A. G. CAUSA, AND R. A. FLEMING, A steel-tire-cord oscillatory-shear dynamic adhesion test (Abstract), (2) 414
VREELAND, J. H., Latex in the coated paper industry (Abstract), (2) 414

WAGNER, M. P., Reinforcing silicas and silicates, (3) 703
WALSH, D. J., see ALLEN, G., (5) 1206
WALTER, G., Elastomers in the automotive industry, (3) 775
WALTER, J. D., see PATEL, H. P., (4) 1095
WARRICK, E. L., Silicone rubber—A perspective (Charles Goodyear medal address, 1976), (4) 909

Weaver, E. J., see Gwin, L. E., (5) 1365
——, see Kachur, V., (5) 1349
Weigmann, H. D., see Lamb, G. E. R., (5) 1145
—— and G. E. R. Lamb, Effects of rubber-curing chemicals on tensile strength of polyester yarns, (4) 1040
Weir, R. J., see Ritchie, K., (2) 408
Weissert, F. C., see Avgeropoulos, G. N., (1) 93
Weissert, F. C., G. N. Avgeropoulos, and G. G. A. Böhm, Heterogeneous polymer blends. II. Physical properties of binary elastomer composites (Abstract), (2) 392
Welch, J. A., see Meyer, D. A., (5) 1362
West, J. C., see Lilaonitkul, A., (5) 1357
West, J. R., see McCormick, C., (5) 1365
Westfahl, J. C., Spectroscopy in the rubber industry, (3) 417
Westley, S. A., Recent developments in novel crosslinking systems for natural rubber (Abstract), (5) 1361
Wewerka, D., K. Hummel, and W. Inselsbacher, Reactions in crosslinked polymers. 3. A metal mold for collecting volatile products during the crosslinking reaction, (5) 1142
White, W. W., Design of SBR latexes for various end applications (Abstract), (2) 411
Wienkoop, G. R., see Kenney, V. R., (2) 399
Winkler, D. S., see Burg, G. R., (2) 397
Witsiepe, W. K., see Hagman, J. F., (2) 395
Wolf, F., see Kainradl, P., (2) 258
Wood, J. Q., see Sutton, N. E., (5) 1353
Wood, L. A., Physical constants of different rubbers, (2) 189
Woods, M. E., and J. A. Davidson, Fundamental considerations for the covulcanization of elastomer blends. II. Lead oxide-activated cures of NBR–EPDM blends, (1) 112

Young, R. N., see Morton, M., (2) 303

Zaiser, G. L., see Goodman, A. L., (5) 1359
Ziegel, K. D., Ozone-resistant blends of EPDM and SBR (Abstract), (2) 393
Zlatkevich, L. Y., Radiothermoluminescence and its application to the study of elastomer structure, (1) 179

SUBJECT INDEX*

Abrasion resistance, relation to tread wear, (1) 12
Abstracts of papers, Fall 1975, (2) 390
  Spring 1976, (5) 1348
Accelerators, effect on polyester cords, (4) 1040
Acrylate–butadiene rubber, by emulsion polymerization, (3) 610
Acrylonitrile–butadiene copolymers, see Nitrile rubber
Acrylonitrile–butadiene–styrene resin (ABS), ethylene–propylene rubber as impact modifier, (4) 978
Adhesion, bonding agents in wire adhesion, (2) 409
  compounding elastomers for, (2) 408
  optimizing wire adhesion, (2) 409
Adhesion test, dynamic, for steel tire cord, (2) 414
Adhesives, peel of joints, (5) 1200
  radial block copolymers for, (5) 1352
Air permeability, of IIR, (4) 967
2-Alkyl-4,6-dichloro-*s*-triazine, properties of, (4) 1031
2-Alkyl-4,6-dithiol-*s*-triazine, neoprene vulcanization, (4) 1031
  toxicology, (4) 1031
Amines, effect on polyester cords, (4) 1040
Aminolysis, of tire cords, (5) 1145
N-(aminothio)imide cure modifiers, effect on rubber compounds, (2) 333
  synthesis, (2) 333
Anisotropy, in fluoroelastomer shrinkage, (1) 35
Anthraquinone, as difunctional coupling agent, (5) 1305
Aramid fibers, reinforcement of rubber, (2) 379
  short fibers in elastomers, (5) 1160
Artificial heart, with polyolefin diaphragm, (5) 1363
Authors, Guide for, (3) G48
Automotive applications, body seals with latex foam, (2) 413
  high-modulus elastomers, (5) 1365
  in tires, belts, hose, etc. (review), (3) 775
  of various polymers (review), (3) 775

Banbury, see Internal mixers
Bearings, elastomers for automotive applications, (3) 775
Bellows seals, elastomers for automotive applications, (3) 775
Best-Paper Awards, Spring 1975, (1) G9
  Fall 1975, (3) G44
  Spring 1976, (5) G80
Black incorporation time (BIT), and molecular weight distribution, (2) 278
  as mixing criterion, (1) 1
  effect of polydispersity, (2) 291
  in SBR, (2) 278
Blends, see also specific materials
  and morphology, (1) 93
  and rheology, (1) 93
  of bromobutyl-modified elastomers, (2) 408
  of elastomers and thermoplastics, (4) 978
  of elastomers, covulcanization, (1) 112
  of EPDM and polydienes, (2) 341
  of EPDM and SBR, ozone resistance, (2) 393
  of NBR and EPDM, (1) 112
  of polymers, heterogeneous, (2) 392
  of SBR, EPDM, and BR, (1) 105
  of thermoplastic rubbers and plastics, (5) 1351
  uniform, of elastomers, (2) 399
  vulcanizate properties of, (1) 112
Block copolymers, from olefinic monomers, (5) 1351
  from tetramethylene oxide and terephthalate, (5) 1357
  microdomain structure, (2) 237
  of silicone rubbers, (4) 909
  polymer interfaces in, (2) 237
Block copolymers, radial, adhesive applications, (5) 1352
  microdomain structure, (2) 237
Blow molding, of copolyester thermoplastic elastomer, (5) 1359
Body seals, elastomers for automotive applications, (3) 775
Bonding agents, in wire adhesion, (2) 409
Book reviews, Emulsion polymerization, (5) G84
  Ionic polymers, (1) G26
  Irradiation in chemical processes, (1) G26
  Physical chemistry, (2) G38
  Physics of rubber elasticity, (5) G85
  Polymer conversion, (2) G37
Bound rubber, determination of, (4) 1019
Brabender Plasticorder, see also Internal mixers, and heterogeneous polymer blends, (1) 93
Brabender Plastograph, see Internal mixers
Branching, in emulsion polymerization (3) 610
  random, in polymers, (5) 1276
Bromobutyl-modified elastomer blends, heat resistance and dynamic properties, (2) 408
Butadiene, as polyfunctional coupling agent, (5) 1305

* Prepared by C. F. Winans.

Butadiene–nitrile rubber, see Nitrile rubber
Butadiene–styrene rubber, see Styrene–butadiene rubber
t-Butenesulfenic acid, as peroxide decomposer, (1) 147
t-Butyl-*t*-butanethiolsulfinate, as peroxide decomposer, (1) 147
t-butyl hydroperoxide, decomposition by sulfur compounds, (1) 147
Butyl rubber (IIR), air permeability, (4) 967
  blends with polyethylene, (4) 978
  in thermoplastic elastomers, (4) 978
  oxidation mechanism, (4) 1010
  physical constants of, (2) 189
  radiothermoluminescence, (1) 179

Calendering, control by computer, (2) 399
Calorimetry, differential scanning (DSC), glass transition of polystyrene, (2) 224
Carbon bisulfide, as solvent for isobutylene copolymers, (4) 960
Carbon black, and fluoroelastomer shrinkage, (1) 43
  effect on fluoroelastomer cure, (1) 43
  effect on mixing of SBR compound, (1) 1
  from pyrolysis of scrap tires, (4) 1120
  identification and determination in vulcanizates, (4) 1060
  in internal mixers, (1) 12
  in polyisoprene mixes, (1) 1
  mixing energy of, (1) 12
  reinforcement by, (1) 12
  structure by electron microscope, (4) 1068
  surface area of, (1) 12
  types, in SBR mixes, (1) 1
Carbon dioxide, from fluoroelastomers during cure, (2) 367
Carboxylated latex, of polychloroprene, (2) 412
Cardiovascular systems, use of rubbers, (5) 1363
Carpet backing, latex in, (2) 414
Cellulose fibers, in elastomers, (5) 1160, 1167
  in EPDM compounds, (5) 1363
  in rubber reinforcement, (5) 1360
Cellulosic pulps, incorporation of latexes, (2) 414
Chicle, polyisoprene microstructure, (5) 1259
Chlorinated polyethylene, heat resistance of, (2) 407
Chlorination, of ethylene–propylene copolymers, (2) 353
2-Chlorocyclohexyl-2′,4′-dinitrophenyl sulfide, (4) 892
bis-Chloromethyl ether, as difunctional coupling agent, (5) 1305
Chloroprene (2-chloro-1,3-butadiene), copolymer with MMA, (2) 394
  copolymers of, (3) 650
  manufacture and chemistry (review), (3) 650
  reactivity with other monomers, (3) 650
  toxicity of, (3) 650
Chloroprene rubber, see Polychloroprene
N-Chlorothioamide adducts, with cyclohexene and hexene, (2) 341
N-Chlorothio-*N*-methyl-*p*-toluenesulfonamide, in cocures of EPDM and polydienes, (2) 341
N-chlorothiophthalimide, in cocure of EPDM and polydienes, (2) 341
Cleaning of curing molds, by vulcanizing special compounds, (5) 1129
Coal fines, in fluoroelastomer, shrinkage, (1) 43
Coated paper, latex in industry, (2) 414
Cocure, curative diffusion in, (1) 112
  of different blend components, (1) 112
  of EPDM and NBR, Pb_3O_4-activated, (1) 112
Composites, of short fibers with elastomers, (5) 1160, 1167
  tire cord–rubber, (4) 1096
Computer, calender control by, (2) 399
  use in curing control, (2) 406
Conjugated dienes, copolymers with isobutylene, (4) 960
Copolyester thermoplastic elastomers, blow molding, (5) 1359
  processing and properties, (5) 1358
Copolymers, of isobutene and conjugated dienes, (4) 960, 967
  of isobutene and isoprene, (4) 937
  of silicone rubber, (4) 909
  preparation and characterization, (2) 394
  spectroscopy of (review), (3) 417
Copolymers, radial block, adhesive applications, (5) 1352
Coordination complexes, of 4,4′-diaminodiphenylmethane, (2) 320
  of 2,3-di(4-aminophenyl)butane, (2) 320
Cord adhesion, dynamic adhesion, (5) 1349
  with isobutylene-diene copolymers, (4) 967
Cotton fibers, reinforcement of rubber, (2) 379
Coupling agents, titanates in filled polymer systems, (2) 398
  titanium derivatives as, (5) 1351
  various compounds as, (5) 1305
Crack growth, effect of solvents on NBR, (5) 1324
Crack resistance, effect of MoS_2 on flexing, (1) 140
Crosslink density, by gas chromatography, (2) 233
  of various elastomers, (2) 233
Crosslinked polymers, collection and analysis of volatiles, (5) 1147
  crack growth in NBR, (5) 1324
Crosslinking, see also Vulcanization
  in emulsion polymerization, (3) 610
  of copolymers of isobutylene and dienes, (4) 960, 967
  of natural rubber, (5) 1361
  of polymer chains, (5) 1219
  of SBR by thiurams, (5) 1193

Crystallization of rubber, calorimetry of, (2) 210
  induced by elongation
Cumene hydroperoxide, decomposition by sulfur compounds, (1) 147
p-Cumyl acetate, in polymer systems, (5) 1350
p-Cumylmethylstyrene, in polymer systems, (5) 1350
Cumylphenol derivatives, (5) 1350
Cure modifiers, *N*-(aminothio)imides, (2) 333
  retardation by phthalic anhydride, (1) 118
Cure rate, in wire adhesion, (2) 409
Cure retardation, by phthalic anhydride, (1) 118
  measurement by scorch time, (1) 118
Curing, see Crosslinking and Vulcanization
Cyclohexane, as solvent for isobutylene copolymers, (4) 960
N-(cyclohexylthio)phthalimide, synthesis and reaction as cure modifier, (2) 333
Cyclopentadiene, copolymer with isobutylene, (4) 960

Deformation, crosslinked rubber, heat of, (2) 210
  of membrane structures, (2) 400
Degradation, of polyester tire cords, (5) 1145
  of thiuram accelerators, (5) 1193
Delta Mooney, as mixing criterion, (1) 1
Density, of amorphous polymers, (2) 207
Determination, of carbon black in vulcanizates, (4) 1060
4,4′-Diaminodiphenylmethane (MDA), applications of, (2) 320
  chemistry of, (2) 320
  coordination complexes, (2) 320
2,3-Di(4-aminophenyl)butane (DPB), coordination complexes of, (2) 320
1,4-Dibromo-2-butene, as difunctional coupling agent, (5) 1305
α,α'-Dibromo-*p*-xylene, as difunctional coupling agent, (5) 1305
Di-*t*-butyl sulfoxide, as peroxide decomposer, (1) 147
α,α'-Dichloro-*p*-xylene, as difunctional coupling agent, (5) 1305
Dicumyl peroxide, in crosslinking polyisoprene, (5) 1142
Die swell, and processability of SBR, (2) 291
  as a mixing criterion, (1) 1
  of SBR–black compounds, (1) 1
Diene functionality, in polyisobutylene, (2) 390
Diene polymers, spectroscopy of (review), (3) 417
Diethylaluminum halides, in isobutene–isoprene copolymerization, (4) 937
Diffraction, in rheo-optical studies (review), (3) 458
α,ω-Dihydroxypolyisoprene, synthesis of, (2) 303
1,4-Diiodo-2-butene, as difunctional coupling agent, (5) 1305
Dimethyldiethoxysilane, hydrolysis of, (4) 909
Dimethyl phthalate, as polyfunctional coupling agent, (5) 1305
Dimethylsiloxane, polymers of, (4) 909
2,4-Dinitrobenzenesulfenyl chloride, for characterization of olefins, (4) 992
N,4-Dinitroso-*N*-methylaniline, reaction with polymers, (4) 1019
Diphenylmethane diisocyanate, formation of polyurethane networks, (5) 1206
Dispersion of ingredients, in mixing, (1) 1
N,N′-dithio-*bis*(morpholine), as scorch inhibitor, (2) 333
Diurethane cure system, in crosslinking NR, (5) 1361
Divinylbenzene, as polyfunctional coupling agent, (5) 1305
Dynamic adhesion, of rubber to cords, (5) 1349
Dynamic stress relaxometer, description of, (2) 247
  estimation of processability, (2) 247

Elasticity, effect of network structure, (5) 1232
  equation for, (5) 1232
Elastomeric block copolymers, morphology, (1) 65
  tear strength of, (1) 65
  tensile strength of, (1) 65
Elastomers, blends of, (1) 105
  blends with thermoplastics, (4) 978
  in cardiovascular research, (5) 1363
  composites with short fibers, (5) 1160
  compounding for adhesion, (2) 408
  crosslink density by gas chromatography, (2) 233
  elongation at low temperature, (4) 1111
  ethylene–acrylic, (2) 395
  flammability of, (1) 158
  heats of combustion, (1) 158
  heterogeneous blends, (2) 392
  high-modulus, in automotive parts, (5) 1365
  homogeneity, (1) 179
  in dynamic cord adhesion tests, (5) 1349
  olefinic linkages in, (4) 992
  oxygen index, (1) 158
  phosphazene for fuel service, (2) 396
  physical constants, (2) 189
  processing of, (5) 1160
  radiothermoluminescence, (1) 179
  reinforcement by cellulose fibers, (5) 1360
  reinforcement by glass fibers, (5) 1350
  reinforcement by silica, (3) 703
  rheology of, (1) 52
  uniform blends of, (2) 399
  viscoelastic properties, (1) 52
Electrical insulation, elastomers for automotive applications, (3) 821
Electron microscope, carbon black structure by scanning and transmission, (4) 1068
Electron spin resonance (ESR), in the rubber industry (review), (3) 417

Elongation, of elastomers at low temperature, (4) 1111
Emulsion polymerization, branching and cross branching, (3) 610
depletion equations, (3) 610
effects of agitation, (3) 610
initiation in monomer droplets, (3) 536
kinetics of (review), (3) 536
mechanism of (review), (3) 536
molecular weight control, (3) 610
of various monomers, (3) 610
Environment, OSHA considerations, (2) 413
Enthalpy of fusion, of polyoctenamer, (1) 170
EPDM-polydiene blends, cocure of, (2) 341
rheometer torque of, (1) 105
solubility of accelerators in, (1) 105
tensile strength of, (1) 105
Ethyl acetate, as difunctional coupling agent, (5) 1305
Ethylene–acrylic elastomer, heat and oil resistance, (2) 395
Ethylene–propylene copolymer, blends with diene rubbers, (2) 353
dehydrohalogenation of, (2) 353
halogenated copolymer, (2) 353
Ethylene–propylene–diene rubber (EPDM), adduct with *N*-chlorothioamides, (2) 341
as impact modifier, (4) 978
automotive applications, (3) 775
blends with SBR for ozone resistance, (2) 393
cellulose fibers in, (5) 1363
in thermoplastic elastomers, (4) 978
NBR blends, cocure, (1) 112
polybutadiene blends, (1) 93
radiothermoluminescence, (1) 179
rheology, (1) 93
shear modulus, (1) 93
vulcanizate properties, (5) 1363
Ethylene–vinyl acetate copolymers, application of rubber compounding technology to, (5) 1359
Extruder, pin type, capability in rubber processing, (2) 403

Fatigue, by rotary flexometer, (2) 258
Feed stocks, for the rubber industry, (5) 1353
Fiber reinforcement, in rubber packing cups, (5) 1360
in V-belt compounds, (5) 1364
Fibers, effect on penetration resistance, (2) 379
effect on physical properties, (2) 379
generated in situ, for reinforcement, (2) 402, (5) 1364
in fluoroelastomers, (1) 43
orientation effect in shrinkage, (1) 43
reinforcement of rubber, (2) 379
Fillers, in fluoroelastomer shrinkage, (1) 43
silane modification, (2) 397
Flammability, of natural and synthetic polymers, (1) 158
Flex life, effect of molybdenum sulfide, (1) 140
Fluorescence, of polymers (review), (3) 458
Fluorescence polarization, of polymers (review), (3) 458
Fluoroelastomers, automotive applications, (3) 775
characterization of, (4) 1001
coefficient of expansion, (1) 35
heat aging, (4) 1001
injection molding of, (5) 1350
production of, (5) 1357
shrinkage of, (1) 35, 43
volatile products from, (2) 367
vulcanization of, (2) 367
weight loss during cure, (2) 367
Fuel service, phosphazene elastomer in, (2) 396
Fungicides, for South American leaf blight, (5) 1360
Fusion enthalpy, of polyoctenamer, (1) 170

Gas chromatography, elastomer crosslink density by, (2) 233
Gel permeation chromatography, characterization of fluororubbers, (4) 1001
distribution of hydroxyl functionality, (5) 1238, 1250
of random branched polymers, (5) 1290
of styrene copolymer with divinyltetrachlorobenzene, (5) 1290
Glass fibers, reinforcement of rubber, (2) 379
Glass transition temperature, by radiothermoluminescence, (1) 179
calorimetry of, (2) 224
of polystyrene, (2) 224
of polyurethanes, (1) 65
Graft copolymers, from olefinic monomers, (5) 1351
of silicone rubber, (4) 909
Grinding, of scrap rubber and plastics, (2) 375
Guide for Authors, (3) G48
Gutta-percha, microstructure of, (5) 1259

Heat of combustion, relation to flammability, (1) 158
Heat generation, effects of external variables, (3) 823
in pneumatic tires, (3) 823
in rotary flexometer, (2) 258
Heat resistance, compounding NBR for, (2) 407
ethylene–acrylic elastomer, (2) 395
of bromobutyl elastomers, (2) 408
of CPE elastomers, (2) 407
Heptane, as cosolvent for isobutylene copolymers, (4) 960
Hexachlorodisilane, as polyfunctional coupling agent, (5) 1305
Hexamethylenetetramine, an alternative for, (2) 408
High-temperature performance, of oil-resistant vulcanizates, (5) 1348
Homogeneity of elastomers, by radiothermoluminescence, (1) 179

Hose, elastomers for automotive applications, (3) 775
Hydrodynamic properties, of random branched polymers, (5) 1276
Hydrogen fluoride, from fluoroelastomers during cure, (2) 367
Hydroplaning, relation to tire friction, (3) 862
Hydroxyl functionality, distribution in polybutadiene, (5) 1238, 1250
Hysteresis, in pneumatic tires, (3) 823
in polyester cords, (5) 1145

Identification, of carbon black in vulcanizates, (4) 1060
Impact modifiers, ethylene–propylene rubber as, (4) 978
polybutadiene as, (4) 978
Infrared spectroscopy, characterization of fluoro rubbers, (4) 1001
dichroism, (3) 458
Fourier transform, (4) 1010
in rheo-optical studies (review), (3) 458
oxidation mechanism of polybutadiene and butyl rubber, (4) 1010
Injection molding, coaxial screw/pot machine, (1) 29
effects of temperature, viscosity, etc., (1) 29
of fluoroelastomers, (5) 1350
Insoluble rubber, determination of, (4) 1019
Internal mixers, Banbury mixers, (1) 12
Brabender Plasticorder, (1) 12
effect of carbon black properties, (1) 12
processing in, (1) 12
scale-up criteria, (1) 1
"unit work" concept, (1) 1
use for SBR-black compounds, (1) 1
Iodine, as difunctional coupling agent, (5) 1305
Isobutylene, bulk polymerization with isoprene and piperylene, (4) 960
copolymer with isoprene, (4) 937
copolymers and networks, (2) 391
Isobutylene–diene copolymers, see also Butyl rubber
for cord adhesion, (4) 967
in sidewall compositions, (4) 967
olefinic linkages in, (4) 992
Isoprene, bulk polymerization with isobutylene, (4) 960
copolymer with isobutylene, (4) 937, 960

Latex, foam for automotive use, (2) 413
for carpet backing, (2) 414
in the coated-paper industry, (2) 414
industry, (2) 419
low-ammonia natural rubber, (2) 410
natural rubber, properties, (2) 410
preparation of artificial, (2) 394
rheological behavior, (2) 411
vulcanization factors, (2) 411
vulcanization of, (2) 413
Layers, thin polymer, on surfaces, (5) 1311
Lead oxide, red, (Pb_3O_4), in cocure of NBR–EPDM blends, (1) 112
Light scattering, of random branched polymers, (5) 1276, 1290
Lithium chloride, in pyrolysis of scrap tires, (4) 1120

Marketing, new products, (5) 1356
Mathematical model, of rubber industry, (5) 1368
Melting temperature, of polyoctenamer, (1) 170
Membrane structures, deformation of, (2) 400
Mercaptobenzothiazole (MBT), reaction with phthalic anhydride, (1) 118
reaction with zinc oxide, (1) 118
Metal oxides and salts, fluoroelastomer shrinkage, (1) 43
Methyl chloride, cocatalyst with diethyl aluminum chloride, (4) 937
as solvent for isobutylene copolymers, (4) 960
Methylchlorosilanes, manufacture of, (4) 909
Methylcyclohexane, as solvent for isobutylene copolymers, (4) 960
Methylene chloride, cocatalyst with diethylaluminum chloride, (4) 967
Methylene iodide, as difunctional coupling agent, (5) 1305
Methyl methacrylate, copolymer with chloroprene, (2) 394
Methylnitroso-*p*-phenylene diamine, pendent groups, (4) 1019
Methyltrichlorosilane, as polyfunctional coupling agents, (5) 1305
Microstructure, of chicle and gutta-percha, (5) 1259
of isoprene–piperylene copolymer, (5) 1269
of polyisoprene, (5) 1259, 1269
Migration, of curing ingredients of blend during cure, (1) 112
Mixers, batch, performance of, (2) 403
Mixers, continuous, performance of, (2) 403
Mixing, and rheology, (1) 93
by pin-type extruder, (2) 403
criteria, (1) 1
in internal mixers, (1) 1
of particulate polymers, (2) 404, (5) 1350
of SBR compounds, (1) 1
of SBR elastomers, (2) 399
scaleup criteria, (1) 1
scorch prevention, (1) 12
shear effects, (1) 12
temperature generation, (1) 12
"unit work" concept for, (1) 1
Mixing efficiency, effect of fill factor, (1) 12
Modulus, equilibrium, of block copolymers, (1) 65
equilibrium, of polyurethanes, (1) 65
Mold for collecting volatiles, in crosslinking reaction, (5) 1142
Mold flash, effect on physical properties, (2) 375
reuse of, (2) 375

Mold fouling, causes of, (5) 1129
Molds, cleaning of, by rubber compounds, (5) 1129
by various means, (5) 1129
Molecular mobility, of thin polymer layers on surfaces, (5) 1311
Molecular weight distribution, and processing of SBR, (2) 291, 278
by gel permeation chromatography, (2) 278, 291, 303
of α,ω-dihydroxypolydienes, (2) 303
Molten salts, pyrolysis of scrap tires in, (4) 1120
Molybdenum disulfide, effect on elastomer flex life, (1) 140
in NR, SBR, and BR blends, (1) 140
in polyurethane, (1) 140
physical property effects, (1) 140
processing characteristics, (1) 140
Mooney viscosity, see Viscosity, Mooney
N-(Morpholinethio)phthalimide, synthesis and reactions, (2) 333
Morphology, of heterogeneous polymer blends, (1) 93
plastic domains in block copolymers, (1) 65
relation to rheology, (1) 93
Mountings, elastomers for automotive applications, (3) 775

Natural rubber, automotive applications, (3) 775
crosslinking system, (5) 1361
design and engineering with, (5) 1362
flammability of, (1) 158
in rotary flexometer, (2) 258
oil-extended, in tire treads, (5) 1362
oxygen index, (1) 158
physical constants of, (2) 189
Neoprene, see Polychloroprene
Networks, see also Polymer networks
Network polymers, interpenetration in isobutylene copolymers, (2) 391
mathematics of, (5) 1219
post-gel properties, (5) 1219
Network structure, effect on elasticity, (5) 1350
effect on equation of elasticity, (5) 1232
of polyisoprene, (2) 303
of polyurethane, (5) 1206
New products, marketing, (5) 1356
Nitrile rubber (NBR), automotive applications, (3) 775
blends with PVC, (4) 978
blends with thermoplastics, (4) 978
compounding for heat resistance, (2) 407
crosslinking and crack growth, (5) 1324
EPDM blends, cocure, (1) 112
in oil-resistant vulcanizates, (5) 1348
in rotary flexometer, (2) 258
radiothermoluminescence, (1) 179
rheology of, (1) 52
solvent crack growth, (5) 1324
Nuclear magnetic resonance (NMR), in the rubber industry (review), (3) 417
of hydrogenated polyisoprene, (5) 1269
of isoprene–piperylene copolymer, (5) 1269
of polyisoprene, (5) 1259, 1269
of polyisoprene–carbon black mixtures, (5) 1182
Nylon, rubber reinforcement by short fibers, (2) 379

Occupational safety and health (OSHA), environmental considerations, (2) 413
Octylphenol–formaldehyde resin, as tackifier, (5) 1365
Oil, extender, effect on mixing of SBR, (1) 1
Oil-resistant vulcanizates, ethylene–acrylic elastomer, (2) 395
high-temperature performance, (5) 1348
Olefinic linkages, distribution in elastomers, (4) 992
in ethylidene–norbornene polymer, (4) 992
in isobutylene–isoprene copolymer, (4) 992
Olefinic monomers, block and graft copolymers from, (5) 1351
Orientation, of short fibers in elastomers, (5) 1160, 1167
Oscillation dampers, elastomers for automotive applications, (3) 775
Oscillatory shear, in steel tire cord adhesion test, (2) 414
Oxidation mechanism, by Fourier-transform infrared, (4) 1010
of polybutadiene, (2) 405
Oxygen index, of polymers, (1) 158
relation to flammability, (1) 158
Ozone cracking, of isobutylene–diene copolymers, (4) 967

Paper pulp, incorporation of latexes, (2) 414
Particulate polymers, see also Powdered SBR
mixing with predispersed pigments, (2) 404
processing behavior, (5) 1350
Peel strength, of adhesive joints, (5) 1200
of rubbers, (5) 1200
Pentane, as solvent for isobutylene copolymers, (4) 960
Phosphazene elastomer, arctic fuel service, (2) 396
Phosphorus trichloride, as polyfunctional coupling agent, (5) 1305
Phthalic anhydride, cure retardation by, (1) 118
reaction with MBT, (1) 118
reaction with zinc oxide, (1) 118
Physical properties, of thermoplastic elastomers, (5) 1355
of various rubbers, (2) 189
Piperylene, copolymer with isobutylene, (4) 960
Plastic domains, in polyurethane elastomers, (1) 65
Plastic fillers, in vulcanizates, (1) 65
Plastomer, see Thermoplastic elastomer

Pollution control, effect on organic chemical manufacture, (5) 1354
review of regulations, (5) 1356
Polyacrylate elastomers, automotive applications (review), (3) 775
Polyacrylonitrile, blends with polybutadiene, (4) 978
Polybutadiene, blends with ethylene–propylene–diene, (1) 93
blends with polyacrylonitrile, (4) 978
emulsion polymerization, (3) 610
hydroxyl-terminated, distribution of functionality, (5) 1238, 1250
infrared study of oxidation, (2) 405
in peel tests, (5) 1200
olefinic linkages in, (4) 992
oxidation mechanism, (4) 1010
rheology of, (1) 93
shear modulus of, (1) 93
Polychloroprene (CR), see also Neoprene
automotive applications, (3) 775
by emulsion polymerization, (3) 610
carboxylated latex, (2) 412
flammability of, (1) 158
heat of combustion, (1) 158
history of (review), (3) 650
latexes, (3) 650
oxygen index, (1) 158
physical constants of, (2) 189
properties and application, (3) 650
review, (3) 650
vulcanization by alkyldithioltriazenes, (4) 1031
Polydimethylsiloxane, see also Silicone
P-V-T data, (2) 200
thin layers on surfaces, (5) 1311
Polydispersity of SBR, relation to black incorporation time, (2) 291
relation to die swell, (2) 291
Polyepichlorhydrin, automotive applications, (3) 775
Polyester cords, crystallization of, (5) 1145
effect of rubber chemicals on (4), 1040
heat generation in, (5) 1145
in dynamic adhesion test, (5) 1349
Polyester fibers, for rubber reinforcement, (2) 379
in V-belt compounds, (5) 1364
Polyethylene, and titanium coupling agents, (5) 1351
blends with butyl rubber, (4) 978
chlorosulfonated, automotive applications, (3) 775
P-V-T data, (2) 200
Polyisobutylene, see also Butyl rubber networks, stress–strain, isotherm, (1) 85
P-V-T data, (2) 200
strain-induced crystallization, (1) 85
with diene functionality, (2) 390
Polyisoprene, black-filled, bound rubber, (5) 1182
black-filled, NMR study, (5) 1182
chicle and gutta-percha, (3) 1259
cis-trans isomerization by uv, (5) 1259
collection and analysis of volatiles during crosslinking, (5) 1142
in blends with EPDM, (2) 341
microstructure, (5) 1269, (2) 303
physical constants of, (2) 189
polymer networks, (2) 303
sequence structure, (5) 1259, 1269
Polymer layers, thin, structure and relaxation, (5) 1311
Polymers, amorphous, density of, (2) 207
from tetramethylene oxide and terephthalate, (5) 1357
gel permeation chromatography, (5) 1290
heats of combustion, (1) 158
heterogeneous blends, (2) 392
homogeneity of, (1) 179
particulate, processing of, (5) 1350
radiothermoluminescence, (1) 179
random branching in, (5) 1276
reaction with dinitrosomethylaniline, (4) 1019
thin layers on surfaces, (5) 1311
Polymer interfaces, in block copolymers, (2) 237
Polymer networks, change of state and entropy, (2) 210
crystallization by elongation, (2) 210
of polyisoprene, (2) 303
Poly(methyl methacrylate), automotive applications, (3) 775
density at high pressure, (2) 207
thin layers on surfaces, (5) 1311
Poly(*o*-methylstyrene), density at high pressure, (2) 207
Polyoctenamer, *cis*-content, (1) 170
crystallization kinetics, (1) 170,
fusion enthalpy, (1) 170
melting temperature, (1) 170
thermodynamic parameters, (1) 170
Polypropylene, blends with elastomers, (4) 978
Polystyrene, blends with elastomers, (4) 978
blends with nitrile rubber, (4) 978
blends with polybutadiene, (4) 978
density at high pressure, (2) 207
glass transition temperature, (2) 224
thin layers on surfaces, (5) 1311
Polyurethane, automotive applications, (3) 775
elongation at low temperature, (4) 1111
glass temperature of, (1) 65
networks, (5) 1206
tear strength of, (1) 65
tensile strength of, (1) 65
thin layers on surfaces, (5) 1311
Polyurethane curatives, from 4,4′-diaminodiphenylmethane, (2) 320
Poly(vinyl acetate), P-V-T data, (2) 200
Poly(vinyl alcohol) fibers, for rubber reinforcement, (2) 379
Poly(vinyl chloride), and titanium coupling agents, (5) 1351
automotive applications, (3) 775
blends with nitrile rubber, (4) 978

Mold fouling, causes of, (5) 1129
Molds, cleaning of, by rubber compounds, (5) 1129
by various means, (5) 1129
Molecular mobility, of thin polymer layers on surfaces, (5) 1311
Molecular weight distribution, and processing of SBR, (2) 291, 278
by gel permeation chromatography, (2) 278, 291, 303
of α,ω-dihydroxypolydienes, (2) 303
Molten salts, pyrolysis of scrap tires in, (4) 1120
Molybdenum disulfide, effect on elastomer flex life, (1) 140
in NR, SBR, and BR blends, (1) 140
in polyurethane, (1) 140
physical property effects, (1) 140
prccessing characteristics, (1) 140
Mooney viscosity, see Viscosity, Mooney
N-(Morpholinethio)phthalimide, synthesis and reactions, (2) 333
Morphology, of heterogeneous polymer blends, (1) 93
plastic domains in block copolymers, (1) 65
relation to rheology, (1) 93
Mountings, elastomers for automotive applications, (3) 775

Natural rubber, automotive applications, (3) 775
crosslinking system, (5) 1361
design and engineering with, (5) 1362
flammability of, (1) 158
in rotary flexometer, (2) 258
oil-extended, in tire treads, (5) 1362
oxygen index, (1) 158
physical constants of, (2) 189
Neoprene, see Polychloroprene
Networks, see also Polymer networks
Network polymers, interpenetration in isobutylene copolymers, (2) 391
mathematics of, (5) 1219
post-gel properties, (5) 1219
Network structure, effect on elasticity, (5) 1350
effect on equation of elasticity, (5) 1232
of polyisoprene, (2) 303
of polyurethane, (5) 1206
New products, marketing, (5) 1356
Nitrile rubber (NBR), automotive applications, (3) 775
blends with PVC, (4) 978
blends with thermoplastics, (4) 978
compounding for heat resistance, (2) 407
crosslinking and crack growth, (5) 1324
EPDM blends, cocure, (1) 112
in oil-resistant vulcanizates, (5) 1348
in rotary flexometer, (2) 258
radiothermoluminescence, (1) 179
rheology of, (1) 52
solvent crack growth, (5) 1324
Nuclear magnetic resonance (NMR), in the rubber industry (review), (3) 417
of hydrogenated polyisoprene, (5) 1269
of isoprene–piperylene copolymer, (5) 1269
of polyisoprene, (5) 1259, 1269
of polyisoprene–carbon black mixtures, (5) 1182
Nylon, rubber reinforcement by short fibers, (2) 379

Occupational safety and health (OSHA), environmental considerations, (2) 413
Octylphenol–formaldehyde resin, as tackifier, (5) 1365
Oil, extender, effect on mixing of SBR, (1) 1
Oil-resistant vulcanizates, ethylene–acrylic elastomer, (2) 395
high-temperature performance, (5) 1348
Olefinic linkages, distribution in elastomers, (4) 992
in ethylidene–norbornene polymer, (4) 992
in isobutylene–isoprene copolymer, (4) 992
Olefinic monomers, block and graft copolymers from, (5) 1351
Orientation, of short fibers in elastomers, (5) 1160, 1167
Oscillation dampers, elastomers for automotive applications, (3) 775
Oscillatory shear, in steel tire cord adhesion test, (2) 414
Oxidation mechanism, by Fourier-transform infrared, (4) 1010
of polybutadiene, (2) 405
Oxygen index, of polymers, (1) 158
relation to flammability, (1) 158
Ozone cracking, of isobutylene–diene copolymers, (4) 967

Paper pulp, incorporation of latexes, (2) 414
Particulate polymers, see also Powdered SBR
mixing with predispersed pigments, (2) 404
processing behavior, (5) 1350
Peel strength, of adhesive joints, (5) 1200
of rubbers, (5) 1200
Pentane, as solvent for isobutylene copolymers, (4) 960
Phosphazene elastomer, arctic fuel service, (2) 396
Phosphorus trichloride, as polyfunctional coupling agent, (5) 1305
Phthalic anhydride, cure retardation by, (1) 118
reaction with MBT, (1) 118
reaction with zinc oxide, (1) 118
Physical properties, of thermoplastic elastomers, (5) 1355
of various rubbers, (2) 189
Piperylene, copolymer with isobutylene, (4) 960
Plastic domains, in polyurethane elastomers, (1) 65
Plastic fillers, in vulcanizates, (1) 65
Plastomer, see Thermoplastic elastomer

Pollution control, effect on organic chemical manufacture, (5) 1354
review of regulations, (5) 1356
Polyacrylate elastomers, automotive applications (review), (3) 775
Polyacrylonitrile, blends with polybutadiene, (4) 978
Polybutadiene, blends with ethylene–propylene–diene, (1) 93
blends with polyacrylonitrile, (4) 978
emulsion polymerization, (3) 610
hydroxyl-terminated, distribution of functionality, (5) 1238, 1250
infrared study of oxidation, (2) 405
in peel tests, (5) 1200
olefinic linkages in, (4) 992
oxidation mechanism, (4) 1010
rheology of, (1) 93
shear modulus of, (1) 93
Polychloroprene (CR), see also Neoprene
automotive applications, (3) 775
by emulsion polymerization, (3) 610
carboxylated latex, (2) 412
flammability of, (1) 158
heat of combustion, (1) 158
history of (review), (3) 650
latexes, (3) 650
oxygen index, (1) 158
physical constants of, (2) 189
properties and application, (3) 650
review, (3) 650
vulcanization by alkyldithioltriazenes, (4) 1031
Polydimethylsiloxane, see also Silicone
P-V-T data, (2) 200
thin layers on surfaces, (5) 1311
Polydispersity of SBR, relation to black incorporation time, (2) 291
relation to die swell, (2) 291
Polyepichlorhydrin, automotive applications, (3) 775
Polyester cords, crystallization of, (5) 1145
effect of rubber chemicals on (4), 1040
heat generation in, (5) 1145
in dynamic adhesion test, (5) 1349
Polyester fibers, for rubber reinforcement, (2) 379
in V-belt compounds, (5) 1364
Polyethylene, and titanium coupling agents, (5) 1351
blends with butyl rubber, (4) 978
chlorosulfonated, automotive applications, (3) 775
P-V-T data, (2) 200
Polyisobutylene, see also Butyl rubber networks, stress–strain, isotherm, (1) 85
P-V-T data, (2) 200
strain-induced crystallization, (1) 85
with diene functionality, (2) 390
Polyisoprene, black-filled, bound rubber, (5) 1182
black-filled, NMR study, (5) 1182
chicle and gutta-percha, (3) 1259
cis-trans isomerization by uv, (5) 1259
collection and analysis of volatiles during crosslinking, (5) 1142
in blends with EPDM, (2) 341
microstructure, (5) 1269, (2) 303
physical constants of, (2) 189
polymer networks, (2) 303
sequence structure, (5) 1259, 1269
Polymer layers, thin, structure and relaxation, (5) 1311
Polymers, amorphous, density of, (2) 207
from tetramethylene oxide and terephthalate, (5) 1357
gel permeation chromatography, (5) 1290
heats of combustion, (1) 158
heterogeneous blends, (2) 392
homogeneity of, (1) 179
particulate, processing of, (5) 1350
radiothermoluminescence, (1) 179
random branching in, (5) 1276
reaction with dinitrosomethylaniline, (4) 1019
thin layers on surfaces, (5) 1311
Polymer interfaces, in block copolymers, (2) 237
Polymer networks, change of state and entropy, (2) 210
crystallization by elongation, (2) 210
of polyisoprene, (2) 303
Poly(methyl methacrylate), automotive applications, (3) 775
density at high pressure, (2) 207
thin layers on surfaces, (5) 1311
Poly(*o*-methylstyrene), density at high pressure, (2) 207
Polyoctenamer, *cis*-content, (1) 170
crystallization kinetics, (1) 170,
fusion enthalpy, (1) 170
melting temperature, (1) 170
thermodynamic parameters, (1) 170
Polypropylene, blends with elastomers, (4) 978
Polystyrene, blends with elastomers, (4) 978
blends with nitrile rubber, (4) 978
blends with polybutadiene, (4) 978
density at high pressure, (2) 207
glass transition temperature, (2) 224
thin layers on surfaces, (5) 1311
Polyurethane, automotive applications, (3) 775
elongation at low temperature, (4) 1111
glass temperature of, (1) 65
networks, (5) 1206
tear strength of, (1) 65
tensile strength of, (1) 65
thin layers on surfaces, (5) 1311
Polyurethane curatives, from 4,4′-diaminodiphenylmethane, (2) 320
Poly(vinyl acetate), P-V-T data, (2) 200
Poly(vinyl alcohol) fibers, for rubber reinforcement, (2) 379
Poly(vinyl chloride), and titanium coupling agents, (5) 1351
automotive applications, (3) 775
blends with nitrile rubber, (4) 978

density at high pressure, (2) 207
impact resistant, (4) 978
Potassium chloride, in pyrolysis of scrap tires, (4) 1120
Powdered SBR, extrusion of, (1) 126
from solution SBR, (1) 126
particle size of, (1) 126
processing effects, (1) 126
Predispersed pigments, mixing with particulate rubbers, (2) 404
Pressure, Volume, Temperature (P-V-T) data
apparatus and test method, (2) 200
of various polymers, (2) 200
Processability, and molecular weight distribution, (2) 278
and rupture energy deformation, (1) 52
and ultimate properties, (1) 52
by die swell, (2) 291
by dynamic stress relaxometer, (2) 247
by Mooney viscometer, (2) 291
of elastomers, (1) 52
of SBR, (2) 278
Processing, see Mixing
i-Propyl tri-*p*-cumyl phenyl titanate, as coupling agent, (5) 1350
Pyrolysis, of scrap tires in molten salts, (4) 1120
of vulcanizates, (4) 1060

Radial block copolymers, adhesives applications, (5) 1352
synthesis of, (5) 1305
Radial tires, cord compression effects and stress analysis, (4) 1095
effect of cord modulus on tread wear, (2) 400
Radiothermoluminescence, glass transition temperature by, (1) 179
homogeneity of elastomers by, (1) 179
Raman polarization, in rheo-optical studies (review), (3) 458
Rayon fibers, reinforcement of rubber, (2) 379
Refraction, in rheo-optical studies (review), (3) 458
Reinforcement of rubber, by carbon black, (1) 12
by cellulose and glass fibers, (5) 1360
by short fibers, (2) 379
by silicas and silicates (review), (3) 703
Relaxation, of thin polymer layers on solids, (5) 1311
stress, instrument, (2) 247
Resorcinol, an alternative for, (2) 407
Retarders, *N*-chlorothioamide adducts, (2) 341
N-chlorothiophthalimide, (2) 341
Rheological properties, of elastomers, (1) 52
of NBR, (1) 52
of SBR, (1) 52
Rheology, in tire tread preparation, (5) 1361
of elastomers, (1) 52
of heterogeneous polymer blends, (1) 93
of latex, (2) 411
of mixing EPDM and BR, (1) 93
relation to morphology, (1) 93
relation to morphology, (1) 93
Reo-optical studies, on polymers (review), (3) 458
Rotary flexometer, fatigue testing, (2) 258
force patterns in, (2) 258
heat generation in, (2) 258
Rubber chemicals, effect on polyester yarns, (4) 1040
Rubber compounding technology, application to EVA copolymers, (5) 1359
Rubber Division, ACS, bylaws, (1) G12
Best Paper Awards, (1) G9, (3) G44, (5) G80
Charles Goodyear Medalist 1976, (4) G75, 909
Guide for Authors, (3) G48
library and information service, (1) G10, (2) G34, (3) G45, (4) G70, (5) G81
officers and committees, (1) G1, (2) G31, (3) G41, (4) G59, (5) G77
policy on technical papers, (3) G47
program for Fall meeting 1976, (4) G62
program for Spring meeting 1976, (1) G5
Rubber industry, feedstocks for, (5) 1353
mathematical model of, (5) 1368
outlook for 1980–1995, (5) 1356
Rubber scrap, grinding for reuse, (2) 375
Rubbers, see Elastomers

Scorch inhibitors, *N*-(aminothio)imides, (2) 333
mechanism of, (2) 333
Scorch time, measurement of cure retardation, (1) 118
Scrap rubber, grinding of, (2) 375
reuse of, (2) 375
Scrap tires, pyrolysis in molten salts and products, (4) 1120
Second power peak, in internal mixer operation, (1) 1
Sequence distribution, by NMR, (5) 1259, 1269
in chicle and gutta-percha, (5) 1259, 1269
in isoprene–piperylene copolymer, (5) 1269
in polyisoprene, (5) 1259, 1269
Shear flow, of short fibers in elastomers, (5) 1160, 1167
Shoe products, use of silica and silicates, (3) 703
Shrinkage of fluoroelastomers, comparison with NBR and EPDM, (1) 35
control of, (1) 43
effects of fillers, (1) 35, 43
fiber orientation effects, (1) 43
measurement of, (1) 35, 43
SI units, use and conversion factors, (1) G25, (2) G36, (3) G56, (4) G76, (5) G83
Sidewall Compositions, with isobutylene–diene copolymers, (4) 967
Silanes, modifiers for fillers, (2) 397
as coupling agents for reinforcement, (3) 703

Silica and Silicates, bonding with elastomers, (3) 703
effect on scorch and cure, (3) 703
effect on viscosity, (3) 703
in rubber reinforcement (review), (3) 703
in shoe products, (3) 703
in tires, (3) 703
surface properties, (3) 703
types and properties of, (3) 703
vulcanizate properties, (3) 703
Silicone rubber, automotive applications, (3) 775
Charles Goodyear Medalist address, (4) 909
discovery, properties and uses, (4) 909
reinforcement by short fibers generated *in situ*, (2) 402, (5) 1364
Silicon tetrachloride, as polyfunctional coupling agent, (5) 1305
Skid resistance, compounding for maximum, (5) 1365
Snow tires, with oil-extended NR, (5) 1362
Solubility, of accelerators, determination, (1) 105
of curing ingredients in solvents, (1) 112
South American leaf blight, control of, (5) 1360
Spectroscopy, in the rubber industry (review), (3) 417
Squalene, reaction with dinitrosomethylaniline (4) 1019
Steel cords, in dynamic adhesion test, (2) 414, (5) 1349
Stereo polymer, semiworks facility, (5) 1353
Stress analysis, of radial tires, (4) 1906
Stress-crack resistance, of polyolefins, (4) 978
of thermoset resins, (4) 978
Stress-optical coefficient, in rheological studies (review), (3) 458
Stress relaxation, characterization of fluororubbers, (4) 1001
dynamic, instrument for, (2) 247
Stress–strain isotherms, of polyisobutylene networks, (1) 85
strain-induced crystallization, (1) 85
temperature effect, (1) 85
Styrene, copolymer with 1,4-divinyl-2,3,5,6-tetrachlorobenzene, (5) 1276
Styrene–acrylonitrile copolymers, impact resistant, (4) 978
Styrene–butadiene latex, end use applications, (2) 411
Styrene–butadiene (SBR) powders, incorporation of pigments, (1) 126
particle size, (1) 126
solution master batch, (1) 126
Styrene–butadiene rubber (SBR), accelerator solubility in, (1) 105
automotive applications, (3) 775
black incorporation time, (2) 278
blends with EPDM for ozone resistance, (2) 393
compounding for tread wear and skid resistance, (5) 1365
die swell as mixing criterion, (1) 1
effect of MW on mixing behavior, (1) 1
emulsion polymerization, (3) 610
in internal mixers, (1) 1
in peel tests, (5) 1200
in rotary flexometer, (2) 258
mixing of, (1) 1, (2) 399
molecular weight distribution, (2) 278
physical constants of, (2) 189
polydispersity, (2) 291
processability, (2) 278
radiothermoluminescence, (1) 179
rheology of, (1) 52
rheometer torque of blends, (1) 105
tensile strength of blends, (1) 105
thiuram vulcanization of, (5) 1193
tread vulcanizate crosslink density, (2) 233
vulcanization of blends, (1) 105
Styrene–butadiene–styrene, block copolymer microdomains, (2) 237
Styrene–isoprene, block copolymer microdomains, (2) 237
Sulfenamide accelerators, effect on polyester cords, (4) 1040
Sulfur compounds, organic, effect of bases on, (1) 147
peroxide decomposers, (1) 147
preventive antioxidants, (1) 147
Sulfur cure, of EPDM-NBR blends, Pb_3O_4 activated, (1) 112

Tackifiers, octylphenol–formaldehyde resin, (5) 1365
Tear strength, of elastomeric block copolymers, (1) 65
of polyurethane, (1) 65
Temperature effects, in fluoroelastomer shrinkage, (1) 43
in injection molding, (1) 29
on tire friction, (3) 823
on tire properties, (3) 823
Tensile strength, effect of temperature, (1) 65
of elastomeric block copolymers, (1) 65
of polyurethane, (1) 65
Terephthalaldehyde, as difunctional coupling agent, (5) 1305
Tetramethylene oxide and terephthalate, block copolymers from, (5) 1357
Tetramethylthiuram disulfide (TMTD), degradation during vulcanization, (5) 1193
in crosslinking of SBR, (5) 1193
in cure of NBR–EPDM blends, (1) 112
solubility of, in methyl ethyl ketone, methylcyclohexane, and elastomers, (1) 112
solubility of Zu, Cd, Pb salts in methyl ethyl ketone and methylcyclohexane, (1) 112
vulcanization mechanism, (5) 1193
Zn, Cd, Pb salts of, in vulcanization, (1) 112
Thermal conductivity, in tires, (3) 823
Thermal expansion, coefficient for fluororubbers, (1) 35

Thermogravimetric analysis (TGA), for identification and determination of carbon black, (4) 1060
Thermoplastic elastomers, blended with other plastics, (5) 1351
butyl rubber with polyethylene, (4) 978
copolyester, applications, (5) 1358
copolyester, processing, (5) 1358, 1359
copolyester, properties, (5) 1358
coupling agents for, (5) 1305,
economics of, (5) 1356
elongation at low temperatures, (4) 1111
ethylene–propylene rubber, (4) 978
injection molding, (5) 1355
synthesis of radial, (5) 1305
weathering of, (5) 1355
Thermoplastics, blends with elastomers, (4) 978
Thiuram accelerators, effect on polyester cords, (4) 1040
Thiuram vulcanizates, effect of cure temperature, (5) 1193
Tire friction, effect of construction, (3) 862
effect of load, (3) 862
effect of road conditions, (3) 862
effect of temperature, (3) 862
effect of velocity, (3) 862
relation to hydroplaning, (3) 862
Tire inflation pressure, effect on cord stress, (4) 1096
Tire treads, compounding for maximum wear, (5) 1365
preparation and rheology, (5) 1361
with oil-extended NR, (5) 1362
Tires, energy loss, (3) 823
heat generation in, (3) 823
hysteresis in, (3) 823
radial, treadwear, (2) 400
reinforcement by silica, (3) 703
temperature profiles in, (5) 1145
thermal conductivity, (3) 823
Titanium coupling agents, effect of functional groups, (5) 1351
in filled polymer systems, (2) 398
Treadwear, radial tires, abrasion resistance, (1) 12
response to cord modulus, (2) 400

Ultimate properties, and mill processability, (1) 52
and rupture energies, (1) 52
and stress–strain at break, (1) 52
Ultrasonics, for cleaning molds, (5) 1129
Ultraviolet spectroscopy, in the rubber industry (review), (3) 449
Uniformity, of elastomer blends, (2) 399

V-Belts, elastomers for automotive applications, (3) 775
fiber-loaded compounds for, (5) 1364
Vinyl polymers, spectroscopy of (review), (3) 417
Viscoelasticity, and ultimate properties, (1) 52
tester for, (5) 1367
Viscosity, intrinsic, of random branched polymers, (5) 1276, 1290
Viscosity, Mooney, effect on mixing in internal mixer, (1) 1
in injection molding, (1) 29
of acrylonitrile–butadiene copolymers, (1) 52
of SBR, (1) 52
relation to mixing energy, (1) 12
Viscosity-work index, as mixing criterion, (1) 1
mixing energy, (1) 12
Visible spectroscopy, in the rubber industry (review), (3) 417
Vulcanizates, accelerator solubility effect, (1) 105
of elastomer blends, (1) 105
with plastic fillers, (1) 65
Vulcanization, see also Crosslinking
control by computer, (2) 406
of EPDM–NBR blends, (1) 112
of latex, (2) 411, 413
of SBR, thiuram accelerated, (5) 1193

Water, from fluoroelastomers during cure, (2) 367
Weathering, of thermoplastic elastomers, (5) 1355
Wire, for reinforcement of rubber, (2) 379
Wire adhesion, bonding agents for, (2) 409
cure rate in, (2) 409
optimization of, (2) 409

X-ray diffraction, of polyisoprenes, (5) 1259

Zinc chloride, in pyrolysis of scrap tires, (4) 1120
Zinc oxide, compared to Pb_3O_4, in cocure of blend, (1) 112
in cocure of NBR–EPDM blends, (1) 112
in cure retardation, (1) 118
reaction with MBT, (1) 118
reaction with phthalic anhydride, (1) 118